**CLASS 1**

Building Product Information Sheet

Product name:

Elephant Standard Plasterboard

Product line *(the product line from which the product is customised)*:

Gypsum plasterboard for general interior linings

Product description and its intended use *(measurements, materials, usage)*:

Elephant Standard is a general-use internal wall and ceiling lining. It is suitable for lining interiors of residential, commercial and industrial buildings.

Available in 10mm & 13mm thickness and 1.2m & 1.35m width. They can range from 2.4 - 6.0m in length.

10mm & 13mm Standard Plasterboards have the same core formulation.

Elephant Standard Plasterboard can be identified by their unique end tapes. The core type & thickness code printed on the face paper is either 'S10' or 'S13' depending on the thickness. These products, when used within a specified Elephant Plasterboard system have performance ratings for specific applications. For full product specs refer to www.elephantplasterboard.co.nz

Product identifier *(if applicable)*:

Unique End Tapes. Core type & thickness code printed on face. Product type/thickness/production date printed on face and back.

Place of manufacture: Aotearoa New Zealand Overseas

Legal and trading name of the manufacturer(s):

KNAUF Siam Gypsum Industries

Legal and trading name of the importer *(if applicable)*:

Elephant Plasterboard New Zealand Limited

Address for service:

STREET NAME 14 Bancroft Crescent

SUBURB Glendene

CITY, COUNTRY Waitakere, New Zealand

POSTCODE 0602

Website:

www.elephantplasterboard.co.nz

Email address:

info@elephantplasterboard.co.nzPhone No. *(if applicable)*:

0800 353 742 or +64 9 8187706

NZBN *(if applicable)*:

9429039045706



Relevant Building Code clauses:

NZBC Clause B1 Structure: B1.3.1, B1.3.2, B1.3.3 (a), (b), (c), (f), (h), (i), (l) and B1.3.4 (a), (b), (d)

NZBC Clause B2 Durability: B2.3.1(a) (i), (ii), and (iii), and B2.3.2.

NZBC Clause C1-C6 Protection from Fire.

NZBC Clause F2 Hazardous Building Materials: F2.3.1

NZBC Clause G6 -Airborne & Impact Sound: G6.3.1

Statement on how the building product is expected to contribute to compliance:


- NZBC Clause B1 Structure: Framing material specifications used with Elephant Plasterboard Systems must be in accordance with the performance requirements of NZBC Clause B1.3.1, B1.3.2, B1.3.3 (a), (b), (c), (f), (h), (i), (l) and B1.3.4 (a), (b), (d). Elephant Standard plasterboard when used and installed in accordance to system specifications outlined in the Elephant QuickBrace Systems technical literature, contributes to providing bracing resistance to light timber and light steel framed buildings subjected to wind or seismic forces.
- NZBC Clause B2 Durability: B2.3.1(a) (i), (ii), and (iii), and B2.3.2. Elephant Plasterboard performance systems have a serviceable life of not less than 50 years when installed in accordance with the relevant Elephant Technical manual specification and in a dry internal environment and when remaining dry in service.
- NZBC Clause C1-C6 Protection from Fire: Elephant Standard Plasterboard used in Elephant Fire & Noise Control wall and floor/ceiling Systems meet the requirements of providing passive fire protection as per NZBC Clause C1-C6.
- NZBC Clause F2 Hazardous Building Materials: Elephant Plasterboard Systems meet this requirement of NZBC Clause F2.3.1 and will not present a health hazard to people, however in order to avoid dust from sanding compounds, use of suitable respiratory protection is recommended.
- NZBC Clause G6 -Airborne & Impact Sound: G6.3.1. Elephant Standard Plasterboard when used in Elephant Noise Control Systems entitled 'Full Intertency' (STC 55 or greater) systems and installed in accordance to Elephant Noise control Systems Technical Manual, meet the requirements of NZBC Clause G6.

- *options for compliance set out in section 19 of the Act (regulations, acceptable solution, verification method)*
- *standard or technical document that describes the performance of the building product or the relevant specifications to which the building product was manufactured*
- *physical properties of the building product*
- *how the building product is intended to be used.*



Limitations on the use of the building product:

It should be noted that Elephant Plasterboard products do not satisfy code requirements on their own, but deliver code compliant performance when used as part of a Elephant Plasterboard systems and installed in accordance to the specific Elephant Plasterboard System specification outlined in the relevant Elephant Plasterboard technical literature.

These products must be handled with care as a finishing material, be installed in a dry internal environment, and remain dry in-service. These sheet materials must not be used in an unprotected external environment, or where there is risk of moisture entry or condensation. 

Design requirements that would support the use of the building product:

Design and installation requirements of Elephant Plasterboard are detailed in the Elephant technical literature below:

Elephant Plasterboard Installation Guide - May 2023
 Elephant QuickBrace Systems Manual - July 2015
 Elephant Plasterboard Fire Rated Systems Manual - March 2023
 Elephant Plasterboard Noise Control System Manual - February 2023
 Elephant Plasterboard Wet Area Systems Manual - July 2017
 Elephant Plasterboard & Fibre Cement Fire Rated Systems Manual - February 2023

Installation requirements:

Refer to Elephant Plasterboard Installation Guide and other relevant Elephant technical manuals listed above available at <https://elephantplasterboard.co.nz/resources-new/>

NZS/AS 2589: 2017 provides further information on installation of Gypsum Linings

Ensure that Elephant Plasterboard is not exposed to moisture during installation and is installed by competent and experienced tradespersons familiar with the installation of Elephant Plasterboard Systems and NZS/AS 2589: 2017



Maintenance requirements:

There are no specific maintenance requirements when Elephant Standard Plasterboard is installed in a dry internal environment and when remaining dry during service. These products must be installed in accordance with the design and installation requirements listed above.

Where Elephant Standard plasterboard replacement is required due to events such as fire, flooding, or excessive structural movement, it must be removed from damaged areas and replaced when remedial work is carried out. Overlay is an option in some situations.

Impact or similar damage sustained by Elephant Standard plasterboard must be re-mediated to ensure Building Code compliance and fire integrity is retained.

For maintenance details following damage to Elephant plasterboard linings, check published literature and/or contact the Elephant information Free phone 0800-353-742

Is the building product/building product line subject to warning or ban under section 26?:

Yes No

If yes, description of the warning or ban under section 26:

Date:

D		D		M		M		Y		Y
---	--	---	--	---	--	---	--	---	--	---